


From the Frame Up, LLC



Tech Tips:

GR - Summary of TC Grease Fittings and Locations:

(Stated size is thread size, not hex head size.)

| Location | Size | Angle | # Req'd | Remarks |
|-------------------------------|----------|--------------|---------|---------------------------------|
| Rear handbrake cable greasers | ¼ BSF | straight | 2 | |
| Drive shaft splined yoke | ¼ BSF | straight | 1 | |
| Universal joints (x-long) | ¼ BSF | straight | 2 | |
| Rear Hubs | 5/16 BSF | straight | 2 | N/A if sealed bearing installed |
| Steering | | | | |
| Front Spring Pin | 5/16 BSF | straight | 2 | |
| Front King Pins | 5/16 BSF | 35 degrees | 4 | |
| Tie Rod Ends | 5/16 BSF | 67 ½ degrees | 2 | |
| Drag Link End | 5/16 BSF | 90 degrees | 2 | |
| Steering Box Cover | 5/16 BSF | straight | 1 | N/A if Tompkins kit installed |
| Water Pump | 5/16 BSF | straight | 1 | |
| Tach drive Rev Counter | 2 BA | straight | 1 | (some) |
| | ¼ BSF | Straight | 1 | (some) |
| | ¼ BSF | 45 degree | 1 | (some) |